# Hand-Arm Vibration Safety

# Policy

April 2013

Reference	Title	Created	Owner	Review
HSWO-	Hand-Arm vibration Policy	01.04.2013	Health, Safety and Wellbeing Office HSWO/JFC	01.04.2013

1

### University of Sussex

### Hand-Arm Vibration Policy

#### **Contents**

- 1. Introduction and Scope
- 2. Purpose
- 3. Definitions
- 4. Responsibilities
- 5. Details of procedure/operational details
- 6. Health Surveillance
- 7. Training
- 8. Monitoring
- 9. References/Related Documents



4

4.5.1 Report any suspect equipment or symptoms to their line manager so that

5.2.5 To allow different exposure patterns to be compared they are adjusted or normalised to a standard reference period of 8 hours, similar to the approach taken for noise levels. The Control of Vibration at Work Regulations 2005 describe how an exposure normalised to 8 hours, A(8), can be calculated. The table below gives the average vibration levels over a working day and the times to reach the exposure levels.

Vibration Magnitude (m/s2)	2.5	3.5	5	7	10	14	20

5.2.7 However, the diversity of work that an individual may be involved in can cause difficulty in accurately assessing exposure because a number of different tools are being used in any one day for variable lengths of time. It should be possible to estimate a cumulative exposure by summing up the typical exposure pattern from the range of equipment used.

the University's Health, Safety and Wellbeing Office who will then inform the Health, Safety & Environment Committee.

The HSE publish a leaflet on HAVS which is a good general information source for employees. Reference IND(G) (rev1) 126L Health risks from hand-arm vibration for employees and the selfemployed (HSE 2002) <u>http://www.hse.gov.uk/pubns/indg296.htm</u> Management of Health and Safety at Work Regulations 1999 The Control of Vibration at Work Regulations 2005

Hand-arm vibration at work: A brief guide <u>http://www.hse.gov.uk/pubns/indg175.htm</u>